



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Amazing Stain Spray Stain Base

Code(s): WS2VB6

Description: Amazing Stain Base is a GREENGUARD certified fast drying spray stain base. It was formulated to be used on wood substrates when blotching is a problem.

Uses: Amazing Stain is a clear stain base that can be tinted using IC800 colorants, dyes, and transparent pigments. M.L. Campbell's Distributor Stain Studio's can tint this base to unlimited stain colors. The recommended tint load is 6% maximum.

Other Products: Amazing Stain can be used under all of M.L. Campbell's clear finish coats.

Physical Properties (packaged) table with rows for Weight per Gallon, % Solids - by Weight, % Solids - by Volume, Flash Point (PMCC), Color, Packaged VOC, and Photochemically Reactive.

Surface Preparation table with rows for New Work and Old Work instructions.

Reduction section with text: No reduction necessary.

Tinting section with text: Stir or shake before tinting. Amazing Stain can be tinted to any stain color to a maximum tint load of 6%; however, Gilsonite cannot be used as a colorant.

Application Procedure section with text: Amazing Stain should be sprayed using low pressure and low volume. Multiple coats can be applied to achieve desired color.

Recoating section with text: After a minimum of 30 minutes air dry, re-coat stain with a selected finish system of lacquer sealer and finish coat. If stain is used to touch up areas, these touch up spots should also be finished for protection.

### Equipment Clean Up

- Use lacquer thinner to clean up all equipment.
- Dispose of dirty solvent and cleaning rags in a safe and approved manner.
- Solvent or lacquer-soaked rags should be stored in water-filled, closed containers prior to disposal.

### Drying Times (at 77°F or 25°C)

**Dry to Touch:** 5 – 10 minutes

### Packaging/Shipping

**Available Units:** Gallons and Pails.

### Shelf Life and Storage

- Do not store around any source of flame or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

### DOT Classification

Flammable Liquid

Red Label

UN 1263

### B/L Description

Paint

UN 1263

Pg II

### Caution

- **THESE PRODUCTS ARE DESIGNED FOR PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*