



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Black Pigmented Lacquer – Flat or Gloss

Table with 4 columns: Code(s), B1532 Flat Black, B1519 Gloss Black, and two empty columns.

Description: M.L. Campbell Black pigmented lacquers are fine quality, pigmented, lightfast lacquers in two popular sheens. They are fast drying with good flow, hiding and adhesion over wood. These lacquers have many versatile job shop applications for store fixtures, window displays, cabinets, trim, and designed furniture.

Physical Properties (packaged) table with 3 columns: Property, B1519 Gloss, B1532 Flat.

Surface Preparation table with 2 columns: Work Type (New/Old) and Description.

Reduction section with 1 column: Description of thinning process.

Application Procedure section with 1 column: Instructions and note on hot spray application.

Drying Time (at 77°F or 25°C) table with 2 columns: Drying Stage and Time.

Packaging/Shipping section with 2 columns: Available Units and Quantity.

Equipment Clean Up

- Use lacquer thinner to clean up all equipment.
- Dispose of dirty solvent and cleaning rags in a safe and approved manner.
- Solvent or lacquer soaked rags should be stored in a water filled, closed containers prior to disposal

Shelf Life and Storage

- 36 month shelf life
- Store in cool, dry areas in the original sealed containers.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification

Flammable Liquid

Red Label

UN1263

B/L Description

Paint

UN1263

3

PG II

Caution

- **THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*