

Product Information (PI) Sheet

Product: Euro Red Catalyst

Code(s) :

| | | | |
|---------|--|--|--|
| EU31377 | | | |
|---------|--|--|--|

Description: Euro Red Catalyst was specially developed for use with EU30178 EuroBild Clear “Wet Look” or EU30278 EuroBild Pigmented “Wet Look” finish systems.

Other Products: Refer to specific Euro system Product Information (PI) Sheets and product labels for proper catalyst mixing ratios, and pot life. This catalyst can have a different mixing ratio depending on the product it is mixed with. This catalyst may react with atmospheric humidity. Reseal can after dispensing catalyst. Once opened use within 1-2 weeks. Some shops use a nitrogen blanket (specialty aerosol product) to protect catalyst from spoilage once opened and resealed. Bloxygen aerosol is one such product.

| Physical Properties (packaged) | |
|----------------------------------|---------------------------|
| Weight per Gallon: | 8.06 lbs. ± .2lbs |
| Flash Point (PMCC): | 25°F or -1°C |
| Packaged VOC: | 626 g/l (5.21 lbs/gallon) |
| Photochemically Reactive: | No |

| Packaging/Shipping | |
|-------------------------|---------------------|
| Available Units: | Quarts and Gallons. |

| Shelf Life and Storage | |
|--|--|
| <ul style="list-style-type: none"> Package life is 18 months. Once opened shelf life is 1-2 weeks. Store in a cool dry area in the original sealed containers. Do not store around any source of flames or sparks. Spills should be cleaned up with non-sparking tools and inert absorbent material. | |

| DOT Classification | | | |
|--------------------|-----------|---------|--|
| Flammable Liquid | Red Label | UN 1263 | |

| B/L Description | | | | |
|-----------------|---------|---|-------|--|
| Paint | UN 1263 | 3 | PG II | |

| Caution | |
|--|--|
| <ul style="list-style-type: none"> THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY. Use only after all safety information is understood. Refer to the Material Safety Data Sheet (MSDS) for additional information. | |

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*