

M.L. Campbell 224 Catherine Street Fort Erie, Ontario L2A 5M9 Canada

Tel: 1(800) 364-1359 Web: <u>www.mlcampbell.com</u>

Product Information (PI) Sheet

Product: Euro Super Slow Retarder

Code(s): EU31697

Description: Euro Super Slow Retarder is a solvent blend designed to lengthen dry times to help

correct any leveling, bubbling and flow issues in extreme tropical and desert

conditions. Euro Super Slow Retarder is the slowest urethane-grade solvent blend M.L.

Campbell offers.

Uses: EU31697 is to be used with EuroBild and Euro X solvent borne polyurethanes at a rate

of 10% to 30%, depending on conditions. Euro Super Slow Retarder can be used in conjunction with or in place of other Euro Reducers or Retarders. The use of retarder will alter the dry time in proportion to the amount added. Excessive use of retarder can increase sheen levels. Do not use in waterborne coatings. Refer to individual Product Information (PI) sheets for correct viscosity profiles.

Physical Properties (packaged)			
Weight per Gallon:	7.26 lbs. ± 0.2		
Flash Point (PMCC):	116° F		
Packaged VOC:	843 g/l (7.03 lb/gal)		
Photochemically Reactive:	No		

Packaging/Shipping				
Available Units:	Gallons.			

Shelf Life and Storage

- Store in cool dry areas in the original sealed containers.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification							
Flammable liquid	Red label	UN1263	3	PGII			

Caution

- THESE PRODUCTS ARE DESIGNED FOR PROFESSIONAL USE ONLY.
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products*.