



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Flattening Compound for Post-Cat Finishes

Table with 4 columns: Code(s), C15801, empty, empty

Description: Flattening base is a high efficient flattening paste for use in post-catalyzed and pre-catalyzed topcoats. Features easy stir in and soft settling. This product is suggested for evaluation. You must determine its suitability and thoroughly quality it for your intended purpose. To use, stir the flattening paste into lacquer until well dispersed. For best results, should only be used in the finish coat. Do not attempt to drop sheen more than 1 sheen level, ex: Gloss to Semi Gloss is ok, but Gloss to Dull is not recommended. Refer to M.L. Campbell Gloss Reduction Chart percentages required.

Table with 2 columns: Physical Properties (packaged), Weight per Gallon: 8.54 lbs. ± .2lbs, % Solids - by Weight: 55 - 57, Flash Point (PMCC): 20 ° F or -7°C, Packaged VOC: 423 g/l (3.53 lbs/gal.), Photochemically Reactive: Yes

Table with 1 column: Application Procedure, You may use up to a maximum of 15% (by weight) of flattening paste to achieve the desired sheen of your product. Flattening Paste is best used to lower the luster's of gloss and semi gloss finishes. Will only make a minimal luster adjustment to satin and dull finishes.

Table with 1 column: Packaging/Shipping, Available Units: Gallons.

Table with 1 column: Shelf Life and Storage, Package life is 24 months - Store in a cool dry area in the original sealed containers. Do not store around any source of flames or sparks. Spills should be cleaned up with non-sparking tools and inert absorbent material.

Table with 3 columns: DOT Classification, Flammable Liquid, Red Label, UN 1263

Table with 4 columns: B/L Description, Paint, UN 1263, 3, PG II

Table with 1 column: Caution, THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY. Use only after all safety information is understood. Refer to the Material Safety Data Sheet (MSDS) for additional information.

### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*