



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: MagnaMax 550 Pre-Catalyzed Pigmented Lacquer

Table with 4 columns and 1 row. Code(s): W119044 Satin

Description: Pigmented MagnaMax 550 is a quality HAPs free, ultra low formaldehyde, low VOC, pre-catalyzed nitrocellulose lacquer formulation (amino, alkyd) and has excellent moisture and chemical resistance.

Uses: MagnaMax 550 Pre-Catalyzed Pigmented Lacquer is a furniture quality lacquer designed for use on Kitchen and bathroom cabinets, dormitory, household, display fixtures and the wood parts of upholstered furniture.

Other Products: MagnaMax 550 Pre-Catalyzed Pigmented Lacquer can be applied as supplied. If reducing is necessary, use C162 1 M.L. Campbell Care Reducer. To slow down drying use M.L. Campbell Care Retarder C161 1. Adding reducers and retarders will increase VOCs.

Table with 2 columns and 13 rows. Title: Physical Properties (packaged). Rows include Weight per Gallon, Viscosity, % Solids, Theoretical Coverage, Flash Point, Color, Sheen, Packaged VOC, and Photochemically Reactive.

Table with 2 columns and 2 rows. Title: Surface Preparation. Rows for New Work and Old Work.

Table with 1 column and 2 rows. Title: Reduction. Row for blushing occurrence.

Table with 1 column and 2 rows. Title: Application Procedure. Rows for equipment suppliers and hot spray application note.

### Equipment Clean Up

- Use lacquer thinner to clean up all equipment.
- Dispose of dirty solvent and cleaning rags in a safe and approved manner.
- Solvent or lacquer-soaked rags should be stored in water-filled, closed containers prior to disposal.

### Drying Times (at 77°F or 25°C)

<b>Dry to Touch:</b>	20-30 minutes
<b>Sanding Dry:</b>	30-45 minutes
<b>Stacking Dry:</b>	12 hours

### Packaging/Shipping

**Available Units:** Gallons and Pails.

### Shelf Life and Storage

- Once catalyzed MagnaMax Pre-catalyzed Pigmented Lacquer 550 g/l has a shelf Life of 120 days.

### DOT Classification

Flammable Liquid	Red label	Un1263		
------------------	-----------	--------	--	--

### B/L Description

Paint	Un1263	PG ii		
-------	--------	-------	--	--

### Caution

- **THESE PRODUCTS ARE DESIGNED FOR PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*