

Product Information (PI) Sheet

Product: Polarion™ Slow Retarder

Code(s) :

MLCPS5			
--------	--	--	--

Description: Polarion Slow Retarder is a solvent blend designed to lengthen dry times to help correct any leveling, bubbling and flow issues in extreme tropical and desert conditions. Polarion Slow Retarder is the slowest urethane-grade solvent blend M.L. Campbell offers.

Other Products: Polarion Slow Retarder is to be used with Polarion series polyurethanes at a rate of 10% to 20% depending on conditions. Polarion Slow Retarder can be used in conjunction with or in place of other Polarion Reducers.

Physical Properties (packaged)	
Weight per Gallon:	7.28 lbs. ± 0.2
Flash Point (PMCC):	97 ° F
Packaged VOC:	859 g/l (7.17 lbs/gallon)
Photochemically Reactive:	No

Application Procedure
The use of reducer will alter the dry time in proportion to the amount added. Excessive use of reducer can increase sheen levels. Do not use in water borne coatings. Refer to individual Product Information (PI) sheets for correct viscosity times.

Packaging/Shipping
Available Units: Gallons

Shelf Life and Storage
<ul style="list-style-type: none"> Store in a cool dry area in the original sealed containers. Do not store around any source of flames or sparks. Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification		
Flammable Liquid	Red Label	UN 1263

B/L Description			
Paint	UN 1263	3	PG II

Caution
<ul style="list-style-type: none"> THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY. Use only after all safety information is understood. Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing
Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes
The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. <i>Thank you for using M.L. Campbell Wood Finishing products.</i>