

SAFETY DATA SHEET

W387214

Section 1. Identification

Product name : STEALTH Clear Base Conversion Varnish
Satin

Product code : W387214

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : M. L. CAMPBELL
101 Prospect Ave. N.W.
Cleveland, OH 44115

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 364-1359

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION (Unborn child) - Category 1B
TOXIC TO REPRODUCTION (Fertility) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 6.9%

GHS label elements

Hazard pictograms



Signal word : Danger

Section 2. Hazards identification

Hazard statements	: Highly flammable liquid and vapor. Causes serious eye damage. Causes skin irritation. May cause cancer. May damage the unborn child. Suspected of damaging fertility. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Contains Formaldehyde - a potential cancer hazard. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.
CAS number/other identifiers	

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
n-Butyl Acetate	17.45	123-86-4
2-Propanol	7.22	67-63-0
Ethanol	6.48	64-17-5
Toluene	6.06	108-88-3
Acetone	5.4	67-64-1
1-Methoxy-2-propanol	4.85	107-98-2
2-Methyl-1-propanol	4.57	78-83-1
Ethyl Acetate	3.03	141-78-6
Dibutyl Phthalate	0.97	84-74-2
1-Methyl-2-Pyrrolidone	0.37	872-50-4
Formaldehyde (max.)	0.01 - 0.1	50-00-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Section 4. First aid measures

- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Contains a formaldehyde-based resin which, under certain conditions of use, may release formaldehyde. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical

Section 7. Handling and storage

(ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
n-Butyl Acetate	<p>ACGIH TLV (United States, 3/2015). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 150 ppm 10 hours. TWA: 710 mg/m³ 10 hours. STEL: 200 ppm 15 minutes. STEL: 950 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 150 ppm 8 hours. TWA: 710 mg/m³ 8 hours.</p>
2-Propanol	<p>ACGIH TLV (United States, 3/2015). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours.</p>
Ethanol	<p>ACGIH TLV (United States, 3/2015). STEL: 1000 ppm 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours.</p> <p>OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.</p>
Toluene	<p>OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes.</p> <p>NIOSH REL (United States, 10/2013).</p>

Section 8. Exposure controls/personal protection

	<p>TWA: 100 ppm 10 hours. TWA: 375 mg/m³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m³ 15 minutes. ACGIH TLV (United States, 3/2015). TWA: 20 ppm 8 hours.</p>
Acetone	<p>ACGIH TLV (United States, 3/2015). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. NIOSH REL (United States, 10/2013). TWA: 250 ppm 10 hours. TWA: 590 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m³ 8 hours.</p>
1-Methoxy-2-propanol	<p>ACGIH TLV (United States, 3/2015). TWA: 50 ppm 8 hours. TWA: 184 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 369 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 360 mg/m³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 540 mg/m³ 15 minutes.</p>
2-Methyl-1-propanol	<p>ACGIH TLV (United States, 3/2015). TWA: 50 ppm 8 hours. TWA: 152 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 50 ppm 10 hours. TWA: 150 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 300 mg/m³ 8 hours.</p>
Ethyl Acetate	<p>ACGIH TLV (United States, 3/2015). TWA: 400 ppm 8 hours. TWA: 1440 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 1400 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours. TWA: 1400 mg/m³ 8 hours.</p>
Dibutyl Phthalate	<p>ACGIH TLV (United States, 3/2015). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 5 mg/m³ 8 hours.</p>
1-Methyl-2-Pyrrolidone	<p>AIHA WEEL (United States, 10/2011). Absorbed through skin. TWA: 10 ppm 8 hours.</p>
Formaldehyde (max.)	<p>ACGIH TLV (United States, 3/2015). Skin sensitizer. Inhalation sensitizer. C: 0.3 ppm C: 0.37 mg/m³ OSHA PEL Z2 (United States, 2/2013).</p>

Section 8. Exposure controls/personal protection

	<p>TWA: 0.75 ppm 8 hours. STEL: 2 ppm 15 minutes. NIOSH REL (United States, 10/2013). TWA: 0.016 ppm 10 hours. CEIL: 0.1 ppm 15 minutes. OSHA PEL (United States, 2/2013). TWA: 0.75 ppm 8 hours. STEL: 2 ppm 15 minutes.</p>
--	--

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
n-Butyl Acetate	<p>CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 200 ppm 15 minutes. 15 min OEL: 950 mg/m³ 15 minutes. 8 hrs OEL: 150 ppm 8 hours. 8 hrs OEL: 713 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 150 ppm 8 hours. TWAEV: 713 mg/m³ 8 hours. STEV: 200 ppm 15 minutes. STEV: 950 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 200 ppm 15 minutes. TWA: 150 ppm 8 hours.</p>
2-Methyl-1-propanol	<p>CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 152 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 50 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 50 ppm 8 hours. TWAEV: 152 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Dibutyl Phthalate	<p>CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 5 mg/m³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013).</p>

Section 8. Exposure controls/personal protection

STEL: 10 mg/m³ 15 minutes.
TWA: 5 mg/m³ 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : Not available.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 55°C (131°F)

Section 9. Physical and chemical properties

Flash point	: Closed cup: -4°C (24.8°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 5.6 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 1% Upper: 19%
Vapor pressure	: 3.2 kPa (23.998 mm Hg) [at 20°C]
Vapor density	: 1.5 [Air = 1]
Relative density	: 0.96
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): >0.205 cm ² /s (>20.5 cSt) Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	
Heat of combustion	: 16.33 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl Acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
2-Propanol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Acetone	LD50 Oral	Rat	5800 mg/kg	-
1-Methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-

Section 11. Toxicological information

2-Methyl-1-propanol	LD50 Oral	Rat	6600 mg/kg	-
	LC50 Inhalation Vapor	Rat	19200 mg/m ³	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
Ethyl Acetate	LD50 Oral	Rat	2460 mg/kg	-
Dibutyl Phthalate	LD50 Oral	Rat	5620 mg/kg	-
1-Methyl-2-Pyrrolidone	LD50 Dermal	Rabbit	8 g/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
Formaldehyde (max.)	LC50 Inhalation Gas.	Rat	250 ppm	4 hours
	LD50 Dermal	Rabbit	270 mg/kg	-
	LD50 Oral	Rat	100 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-Butyl Acetate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
2-Propanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
Ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
Toluene	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
Acetone	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
	Eyes - Mild irritant	Human	-	186300 parts per million	-
	Eyes - Mild irritant	Rabbit	-	10 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Section 11. Toxicological information

1-Methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	395 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
1-Methyl-2-Pyrrolidone	Skin - Mild irritant	Rabbit	-	500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
Formaldehyde (max.)	Eyes - Mild irritant	Human	-	6 minutes 1 parts per million	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	750 Micrograms	-
	Skin - Mild irritant	Human	-	72 hours 150 Micrograms Intermittent	-
	Skin - Severe irritant	Human	-	0.01 Percent	-
	Skin - Mild irritant	Rabbit	-	540 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 50 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
2-Propanol	-	3	-
Ethanol	-	1	-
Toluene	-	3	-
Formaldehyde (max.)	+	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-Propanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Ethanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Section 11. Toxicological information

Acetone	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
1-Methoxy-2-propanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2-Methyl-1-propanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Formaldehyde (max.)	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
2-Propanol	Category 2	Not determined	Not determined
Ethanol	Category 2	Not determined	Not determined
Toluene	Category 2	Not determined	Not determined
Acetone	Category 2	Not determined	Not determined
1-Methoxy-2-propanol	Category 2	Not determined	Not determined
2-Methyl-1-propanol	Category 2	Not determined	Not determined
Formaldehyde (max.)	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 stomach pains
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : May damage the unborn child.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	7800.3 mg/kg
Dermal	74472.2 mg/kg
Inhalation (vapors)	420.5 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
n-Butyl Acetate	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	2-Propanol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon
Ethanol	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna -	21 days

Section 12. Ecological information

Toluene	Chronic NOEC 0.375 µl/L Fresh water	Neonate Fish - Gambusia holbrooki - Larvae	12 weeks
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
Acetone	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 7200000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 6900 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
2-Methyl-1-propanol	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Acute EC50 1200000 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata - Larvae	48 hours
Ethyl Acetate	Acute LC50 1030000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1330000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 4000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 2500000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 750000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 154000 µg/l Fresh water	Daphnia - Daphnia cucullata	48 hours
	Acute LC50 212500 µg/l Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Dibutyl Phthalate	Chronic NOEC 75.6 mg/l Fresh water	Fish - Pimephales promelas - Embryo	32 days
	Acute EC50 3.4 µg/l Marine water	Algae - Gymnodinium breve	96 hours
	Acute EC50 2990 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
1-Methyl-2-Pyrrolidone	Acute LC50 480 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 210 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 500 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 25 µg/l Fresh water	Fish - Danio rerio - Embryo	5 weeks
	Acute LC50 1.23 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 832 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
Formaldehyde (max.)	Acute EC50 3.48 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Acute EC50 0.788 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 12.98 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 5800 µg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 1.41 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.005 mg/l Marine water	Algae - Isochrysis galbana - Exponential growth phase	96 hours
	Chronic NOEC 953.9 ppm Fresh water	Fish - Oncorhynchus tshawytscha - Egg	43 days

[Persistence and degradability](#)

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-Butyl Acetate	-	-	Readily
2-Propanol	-	-	Readily
Ethanol	-	-	Readily
Toluene	-	-	Readily
Acetone	-	-	Readily
1-Methoxy-2-propanol	-	-	Readily
2-Methyl-1-propanol	-	-	Readily
Ethyl Acetate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Ethyl Acetate	-	30	low
Dibutyl Phthalate	-	165.96	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II

Date of issue/Date of revision : 6/4/2016 **Date of previous issue** : 6/3/2016 **Version** : 3 16/18

Section 14. Transport information

Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	-	-	Emergency schedules (EmS) F-E, S-E
	ERG No. 128	ERG No. 128	ERG No. 128		

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Procedure used to derive the classification

Classification

Justification

Section 16. Other information

FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 1B	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

History

Date of printing : 6/4/2016

Date of issue/Date of revision : 6/4/2016

Date of previous issue : 6/3/2016

Version : 3

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.